

SOLUNA™

POWER DESIGNED FOR NIGHT AND DAY

SOLUNA™

POWER DESIGNED FOR NIGHT AND DAY



SOLUNA™

www.soluna.co

Email: sales@solunabattery.com

Tel: +86-21-57475835

SOLUNA™

www.soluna.co

Email: sales@solunabattery.com

Tel: +86-21-57475835

Soluna Franz 9.6K PACK LV is a battery solution ideal for residential and small commercial energy storage applications.

The model is adopted by the latest LiFePO4 technology with an intelligent BMS integrated in the fault protection for energy security, offering a capacity of 9.6kWh which can be installed in parallel up to 12 batteries allowing 115.2kWh of total storage.

With a 10-year warranty and 6000 cycle life, the Soluna Franz 9.6K PACK LV is a flexible, reliable and high performance battery storage solution.

Low Voltage



Scalable to 115.2 kWh

Safest LiFePO4 battery



Long lifespan

Easy Installation



Floor, Wall mounting



TECHNICAL SPECIFICATIONS

PHYSICAL CHARACTERISTICS

Height (mm)	760
Width (mm)	500
Depth (mm)	215
Weight (kg)	90
Installation	Indoor / Outdoor

ELECTRICAL CHARACTERISTICS

Battery type	Lithium LFP
Nominal Capacity(kWh)	9.6
Usable Energy (kwh)[1]	9.6
Nominal voltage (V)	48
Voltage range (usable) (V)	45 to 54
Max. charge/ discharge current(A)	100 / 200
Depth of discharge (DoD) (%)	90
Internal resistance (mΩ)	≤60
Cycle life	≥6000
Battery pack round-trip efficiency (%)	>95
DC disconnect	Contactors / fuse

BMS

Power consumption	<3W (work) <100 mW (sleep)
Monitoring parameters	System voltage System current Cell voltage Cell temperature CAN
Communication	CAN

OPERATING CONDITIONS

Operating temperature (°C)	-10 to 50
Operating temperature(recommended) (°C)	15 to 30
Storage temperature (recommended)(°C)	-20 to 60
Humidity conditions(%)	5 to 95
Altitude(m)	Max. 2,000
Cooling strategy	Natural convection

RELIABILITY AND CERTIFICATION

Certification	Cell: UL1642 Module: IEC62619, UN38.3 CE ROHS
Transportation	UN38.3
Ingress protection rating	IP 55
System configuration	1 to 12 parallel

WARRANTY

Product and performance	10-year standard warranty
-------------------------	---------------------------

[1] Test conditions: 100% DOD of nominal capacity, 0.2C charge & discharge at +25°C. Battery usable energy may vary with different inverter brand